

NOMAD PORTABLE POWER & LIGHTING DISTRIBUTION SYSTEMS



WWW.PDC.CO.NZ

Christchurch Office

PO Box 9022
388 - 396 Tuam St, Phillipstown,
Christchurch 8011
New Zealand

P +64 3 335 0366

F +64 3 335 0980

E switchboards@pdc.co.nz

Northern Region/Auckland

PO Box 12 249
30 Fairfax Ave, Penrose, Auckland
1061
New Zealand

P +64 9 526 7881

F +64 9 579 8742

E switchboards@pdc.co.nz

NOMAD N32 & N63 SERIES



LIGHTING | POWER | DISTRIBUTION | AUTOMATION

N32 Series



The **Nomad 32 (N32)** is ideally used as a standalone distribution centre or interconnected with other Nomad products, providing a flexible system for any construction site, outdoor or trade event. The Nomad 32 is supplied with 9 single phase, 1 three phase and 1 interconnection sockets. All single phase sockets outlets are RCD protected.

N32			
OUTLETS	QUANTITY	VOLTAGE	CONFIGURATION
32A*	1	400V	IEC, 3PH + E + N
16A	1	230V	IES, 2P + E (RCD PROTECTED)
15A	2	230V	AS/NZ, 2P + E (RCD PROTECTED)
10A	6	230V	AS/NZ, 2P + E (RCD PROTECTED)
WEIGHT		INPUT	
16KG		1 X 32A, 400V, 3PH + E + N	

*Interconnection outlets

N63 Series



The **Nomad 63 (N63)** provides the 63A distribution hub for the Nomad system. Suitable for large or small construction project, Nomad 63 can be used alone or interconnected with other Nomad products. Supplied with 5 single phase, 1 three phase with RCD protecting and 2 interconnection socket outlets. All single phase sockets outlets are RCD protected.

N63			
OUTLETS	QUANTITY	VOLTAGE	CONFIGURATION
63A*	1	400V	IEC, 3PH + E + N
32A*	1	400V	IEC, 3PH + E + N
32A	1	400V	AS/NZ, 2P + E (RCD PROTECTED)
16A	1	230V	AS/NZ, 2P + E (RCD PROTECTED)
15A	1	230V	AS/NZ, 2P + E (RCD PROTECTED)
10A	3	230V	AS/NZ, 2P + E (RCD PROTECTED)
WEIGHT		INPUT	
17KG		1 X 63A, 400V, 3PH + E + N	

*Interconnection outlets